



This valve is a normally closed, electro-proportional, blocking poppet throttle that is spring-biased closed. Energizing the coil generates an opening force on the poppet proportional to the command current, and this force is countered by the spring and flow forces. This force balance creates a metering orifice whose effective size is proportional to the current. The valve exhibits a large degree of self-compensation in the 2-to-1 direction and will provide proportional flow control in the 1-to-2 direction with the addition of an external compensator. Full reverse flow (1-to-2) with 100% command in the 1-to-2 direction is possible without a compensator under all conditions.

## TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.@350 bar
Viscosity Range	2,8 - 380 cSt
Response Time - Typical	50 ms
Switching Frequency	15,000 max. cycles/hr
Seal kit - Cartridge	Buna: 990162007
Seal kit - Cartridge	Viton: 990162006

## NOTES

- Please verify cartridge clearance requirements when choosing a Sun manifold. Different valve controls and coils require different clearances.
- An additional 2.00 inches (50,8 mm) beyond the valve extension is needed for coil installation and removal.

## CONFIGURATION OPTIONS

### Model Code Example: FPBUXCN

CONTROL	(X)	FLOW RATE	(C)	SEAL MATERIAL	(N)	COIL *
<b>X</b> No Manual Override		<b>C</b> Nominal 2.6 gpm @ 200 psi (14 bar) differential (9.8 L/min) (9,8 L/min.)		<b>N</b> Buna-N		No coil
<b>M</b> Manual Override				<b>V</b> Viton		

\* Additional coil options are available