



Three-position, 4-way directional cartridges are spring-centered, 6-port directional valves that can be configured from a choice of 10 different spool options. The supply port is port 1 and all ports will accept 5000 psi (350 bar). Capacity for these pilot-to-shift valves is dependent on the spool type specified.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Minimum Pilot Pressure Required to Shift Valve	12 bar
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min. @70 bar
Pilot Volume Displacement	0,33 cc
Seal kit - Cartridge	Buna: 990061007
Seal kit - Cartridge	Polyurethane: 990061002
Seal kit - Cartridge	Viton: 990061006

CONFIGURATION OPTIONS

Model Code Example: DCCAXCN

CONTROL	(X) SPOOL CONFIGURATION	(C) SEAL MATERIAL	(N)
X Standard Pilot	C Blocked Center	N Buna-N	
D Vent to Operate	A A to T Center	V Viton	
	B B to T Center		
	G Regen w/ Blocked Center		
	H Open Center		
	N P to A and B to T Center		
	R Regen Center		
	T Tandem Center		
	W A and B Bleed to T Center		
	X P to B and A to T Center		
	Y A and B to T Center		