



Two-position, 3-way directional cartridges are 6-port (port 5 is not used) directional valves that can be configured with up to 5 different spool configurations. The supply port is port 3 and all ports will accept 5000 psi (350 bar). Capacity for these pilot-to-shift valves is dependent on the spool type specified.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Minimum Pilot Pressure Required to Shift Valve	20 bar
Pilot Pressure Required for Full Shift at Rated Flow	24 bar
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	50 cc/min.@70 bar
Pilot Volume Displacement	4,4 cc
Seal kit - Cartridge	Buna: 990054007
Seal kit - Cartridge	Polyurethane: 990054002
Seal kit - Cartridge	Viton: 990054006

CONFIGURATION OPTIONS

Model Code Example: DDHGXCN

CONTROL	(X)	SPOOL CONFIGURATION	(C)	SEAL MATERIAL	(N)
X Not Adjustable		C Closed Crossover		N Buna-N	
		O Open Crossover		V Viton	
		R Restricted Crossover			
		Y All Ports Blocked			
		Z All Ports Open			