



Fixed-orifice, pressure-compensated flow controls provide precise flow regulation for meter-in or meter-out applications where there may be wide pressure fluctuations. The flow setting is specified by the user and is set at the factory.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                            |                         |
|----------------------------|-------------------------|
| Maximum Operating Pressure | 350 bar                 |
| Locknut Hex Size           | 15 mm                   |
| Locknut Torque             | 9 - 10 Nm               |
| Seal kit - Cartridge       | Buna: 990010007         |
| Seal kit - Cartridge       | EPDM: 990010014         |
| Seal kit - Cartridge       | Polyurethane: 990010002 |
| Seal kit - Cartridge       | Viton: 990010006        |

**CONFIGURATION OPTIONS**

**Model Code Example: FXCAXAN**

| <b>CONTROL</b>             | <b>(X) SETTING RANGE</b>                                  | <b>(A) SEAL MATERIAL</b> | <b>(N) MATERIAL/COATING</b>     |
|----------------------------|---|--------------------------|---------------------------------|
| <b>X</b> Not Adjustable    | <b>A</b> Replaceable Orifice .1 - 6 gpm (0,4 - 23 L/min.) | <b>N</b> Buna-N          | Standard Material/Coating       |
| <b>L</b> Tuning Adjustment |   | <b>E</b> EPDM            | /AP Stainless Steel, Passivated |
| <b>K</b> Handknob          |   | <b>V</b> Viton           | /LH Mild Steel, Zinc-Nickel     |