



The relief-after-check cartridge is a CavitySaver™ (multi-function) valve incorporating a direct-acting relief tee'd in after a check function. The check valve flow is from the inlet (port 2) to the system port (port 1). When the pressure in the system (port 1) reaches the relief valve setting, the valve starts to open to tank (port 3), throttling flow to limit the pressure rise. These valves are smooth and quiet, essentially zero-leak, dirt-tolerant, immune to silting and are very fast.

## TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Factory Pressure Settings Established at	15 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at Reset	0,3 cc/min.
Check Cracking Pressure	1,7 bar
Response Time - Typical	10 ms
Adjustment - No. of CW Turns from Min. to Max. setting	6
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990011007
Seal kit - Cartridge	Polyurethane: 990011002
Seal kit - Cartridge	Viton: 990011006

## CONFIGURATION OPTIONS

### Model Code Example: HRDBLAN

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
<b>L</b> Standard Screw Adjustment	<b>A</b> 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting	<b>N</b> Buna-N	Standard Material/Coating
<b>C</b> Tamper Resistant - Factory Set		<b>V</b> Viton	/AP Stainless Steel, Passivated
<b>K</b> Handknob	<b>W</b> 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar) Standard Setting		/LH Mild Steel, Zinc-Nickel