



Pilot-operated, anti shock relief cartridges limit maximum system pressure and also limit the rate of pressure rise. The valve opens and then ramps closed at a constant speed, independent of settings and flows. The adjust screw determines the maximum (relief) setting and the minimum (threshold) setting.

## TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Factory Pressure Settings Established at	15 L/min.
Maximum Operating Pressure	350 bar
Control Pilot Flow	0,16 - 0,41 L/min.
Pressure Ramp Up Time	400 - 600 ms
Response Time - Typical	2 ms
Adjustment - No. of CW Turns from Min. to Max. setting	4.5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
U.S. Patent #	6,039,070
Seal kit - Cartridge	Buna: 990318007
Seal kit - Cartridge	Viton: 990318006

## CONFIGURATION OPTIONS

### Model Code Example: RPKTLAN

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>L</b> Standard Screw Adjustment		<b>A</b> 2000 - 3000 psi (140 - 210 bar), 2000 psi (140 bar) Standard Setting		<b>N</b> Buna-N		Standard Material/Coating
<b>C</b> Tamper Resistant - Factory Set		<b>C</b> 4500 - 6000 psi (315 - 420 bar), 4500 psi (315 bar) Standard Setting		<b>V</b> Viton		/AP Stainless Steel, Passivated
		<b>W</b> 3000 - 4500 psi (210 - 315 bar), 3000 psi (210 bar) Standard Setting				