


3-Port Atmospherically Referenced, Non-adjustable



These valves are self-setting counterbalance valves which combine multiple functions in one package; reverse free flow, load, and thermal relief. The check allows free flow from the directional valve (port 2) to the load (port 1) while a direct-acting pilot function self adjusts to approximately 1.3 times the load induced pressure up to the thermal relief setting.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Factory Pressure Settings Established at	30 cc/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at Reseat	0,3 cc/min.
Check Cracking Pressure	1,7 bar
Reseat	>85% of setting
Seal kit - Cartridge	Buna: 990011007
Seal kit - Cartridge	Viton: 990011006

**NOTES** Patents are pending for this product.

**CONFIGURATION OPTIONS**

**Model Code Example: MADPDHN**

CONTROL	(D) FACTORY SET	(H) SEAL MATERIAL	(N)
<b>D</b> LoadMatch™	<b>H</b> 4000 psi (280 bar) <b>G</b> 6000 psi (420 bar) <b>J</b> 5000 psi (350 bar)	<b>N</b> Buna-N <b>V</b> Viton	