



Free-flow, side-to-nose check valves are on/off circuit components that allow free flow from the inlet (port 2) to the outlet (port 1) and block flow in the opposite direction.

### TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                            |                  |
|----------------------------|------------------|
| Maximum Operating Pressure | 210 bar          |
| Seal kit - Cartridge       | Buna: 990203007  |
| Seal kit - Cartridge       | Viton: 990203006 |

### CONFIGURATION OPTIONS

Model Code Example: CXECXCN

| CONTROL                      | (X) | CRACKING PRESSURE         | (C) | SEAL MATERIAL   | (N) |
|------------------------------|-----|---------------------------|-----|-----------------|-----|
| <b>X</b> External 6-SAE Port |     | <b>C</b> 30 psi (2 bar)   |     | <b>N</b> Buna-N |     |
|                              |     | <b>A</b> 4 psi (0,3 bar)  |     | <b>V</b> Viton  |     |
|                              |     | <b>B</b> 15 psi (1 bar)   |     |                 |     |
|                              |     | <b>D</b> 50 psi (3,5 bar) |     |                 |     |
|                              |     | <b>E</b> 75 psi (5 bar)   |     |                 |     |
|                              |     | <b>F</b> 100 psi (7 bar)  |     |                 |     |
|                              |     | <b>Z</b> 1 psi (0,07 bar) |     |                 |     |