



Normally closed modulating elements with an internal orifice between port 1 and port 3 can be used as a main-stage relief valve. The valve can be controlled remotely using a pilot relief or pilot solenoid valve.

### TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Control Pilot Flow	0,25 - 0,50 L/min.
Control Orifice Diameter	0,53 mm
Seal kit - Cartridge	Buna: 990017007
Seal kit - Cartridge	Polyurethane: 990017002
Seal kit - Cartridge	Viton: 990017006

### CONFIGURATION OPTIONS

Model Code Example: LRHAXHN

CONTROL	(X) BIAS PRESSURE	(H) SEAL MATERIAL	(N) MATERIAL/COATING
<b>X</b> Not Adjustable	<b>H</b> 200 psi (14 bar)	<b>N</b> Buna-N	Standard Material/Coating
<b>E</b> External 4-SAE Port, Port 3 blocked	<b>D</b> 50 psi (3,5 bar)	<b>V</b> Viton	/AP Stainless Steel, Passivated
<b>L</b> Tuning Adjustment	<b>F</b> 100 psi (7 bar)		
	<b>G</b> 150 psi (10,5 bar)		