



Fixed-orifice, pressure-compensated flow controls provide precise flow regulation for meter-in or meter-out applications where there may be wide pressure fluctuations. A variety of flow rates are available.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Valve Internal Hex Size	8 mm
Seal kit - Cartridge	Buna: 990008007
Seal kit - Cartridge	Polyurethane: 990008002
Seal kit - Cartridge	Viton: 990008006

**CONFIGURATION OPTIONS**

Model Code Example: **FXAGXAN**

CONTROL	(X) FLOW RATE	(A) SEAL MATERIAL	(N)
<b>X</b> Not Adjustable	<b>A</b> 15 in <sup>3</sup> /min. (250 cc/min.)	<b>N</b> Buna-N	
	<b>B</b> 20 in <sup>3</sup> /min. (330 cc/min.)	<b>V</b> Viton	
	<b>D</b> 40 in <sup>3</sup> /min. (660 cc/min.)		
	<b>F</b> 60 in <sup>3</sup> /min. (1 L/min.)		
	<b>H</b> 80 in <sup>3</sup> /min. (1.3 L/min.)		
	<b>J</b> 100 in <sup>3</sup> /min. (1.6 L/min.)		
	<b>L</b> 120 in <sup>3</sup> /min. (2.0 L/min.)		