



This valve is a 4-way, 3-position proportional directional valve. Work ports 2 and 4 are drained to 5 in the center position and port 3 is closed. Pilot pressure at port 1 opposes the spring and creates a variable metering orifice between ports 3 and 4 that is proportional to the pressure at 1. Piloting 6 opens 3 to 2. The force balance of the flow forces, spring and pilot pressure results in a degree of partial self-compensation as the load pressure changes.

Pressure at ports 1 and 6 directly oppose each other.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Pilot Pressure Required for Full Shift at Rated Flow	20 - 23 bar
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	131 cc/min.@70 bar
Pilot Volume Displacement	1,8 cc
Seal kit - Cartridge	Buna: 990053007
Seal kit - Cartridge	Viton: 990053006

CONFIGURATION OPTIONS

Model Code Example: FTFCXYN

CONTROL	(X)	SPOOL CONFIGURATION	(Y)	SEAL MATERIAL	(N)	MATERIAL/COATING
X Not Adjustable		Y A and B to T Center W A and B Bleed to T Center		N Buna-N V Viton		Standard Material/Coating JAP Stainless Steel, Passivated