



Pilot-operated, anti shock relief cartridges limit maximum system pressure and also limit the rate of pressure rise. The valve opens and then ramps closed at a constant speed, independent of settings and flows. The adjust screw determines the maximum (relief) setting and the minimum (threshold) setting.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Factory Pressure Settings Established at	15 L/min.
Maximum Operating Pressure	350 bar
Control Pilot Flow	0,16 - 0,41 L/min.
Pressure Ramp Up Time	200 - 400 ms
Response Time - Typical	2 ms
Adjustment - No. of CW Turns from Min. to Max. setting	4.5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
U.S. Patent #	6,039,070
Seal kit - Cartridge	Buna: 990303007
Seal kit - Cartridge	Polyurethane: 990303002
Seal kit - Cartridge	Viton: 990303006

NOTES Patents: US#6,039,070; Germany EP 1 001 197; Japan #3,119,230

CONFIGURATION OPTIONS

Model Code Example: RPGTLAN

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
L Standard Screw Adjustment	A 2000 - 3000 psi (140 - 210 bar), 2000 psi (140 bar) Standard Setting	N Buna-N	Standard Material/Coating
C Tamper Resistant - Factory Set	C 4500 - 6000 psi (315 - 420 bar), 4500 psi (315 bar) Standard Setting	V Viton	/AP Stainless Steel, Passivated
	W 3000 - 4500 psi (210 - 315 bar), 3000 psi (210 bar) Standard Setting		/LH Mild Steel, Zinc-Nickel