



This solenoid controlled, 2-way, 2-position cartridge is a pilot-operated, poppet style directional valve with reverse free flow check. It is available in either a normally open or normally closed configuration. Due to its poppet style construction, it has extremely low leakage.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min. @350 bar
Check Cracking Pressure	3,5 bar
Response Time - Typical	30 ms
Switching Frequency	15,000 max. cycles/hr
Seal kit - Cartridge	Buna: 990310007
Seal kit - Cartridge	EPDM: 990313014
Seal kit - Cartridge	Viton: 990310006

NOTES

- Please verify cartridge clearance requirements when choosing a Sun manifold. Different valve controls and coils require different clearances.
- An additional 2.00 inches (50,8 mm) beyond the valve extension is needed for coil installation and removal.

CONFIGURATION OPTIONS

Model Code Example: DACCMCN

CONTROL	(M) SPOOL CONFIGURATION	(C) SEAL MATERIAL	(N) COIL *
M Manual Override	C Normally Closed	N Buna-N	No coil
C Concealed Manual Override	H Normally Open	E EPDM	212 DIN 43650-Form A, 12 VDC
		V Viton	224 DIN 43650-Form A, 24 VDC

* Additional coil options are available