



Ventable, pilot-operated, balanced piston relief cartridges with external drain are normally closed pressure regulating valves. When the pressure at the inlet (port 1) reaches the valve setting, the valve starts to open to tank (port 2), throttling flow to regulate the pressure. They provide a vent port (port 3) that connects between the main piston and pilot stage to provide for remote control by other pilot or 2-way valves and a drain (port 4) that makes them insensitive to back pressure. These valves are accurate, have low pressure rise vs. flow, they are smooth and quiet, and are moderately fast.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|--------------------------------------------------------|-------------------------|
| Factory Pressure Settings Established at | 15 L/min. |
| Maximum Operating Pressure | 350 bar |
| Control Pilot Flow | 0,16 - 0,25 L/min. |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 50 cc/min. @70 bar |
| Response Time - Typical | 10 ms |
| Adjustment - No. of CW Turns from Min. to Max. setting | 5 |
| Locknut Hex Size | 15 mm |
| Locknut Torque | 9 - 10 Nm |
| Seal kit - Cartridge | Buna: 990022007 |
| Seal kit - Cartridge | Polyurethane: 990022002 |
| Seal kit - Cartridge | Viton: 990022006 |

CONFIGURATION OPTIONS

Model Code Example: RVEDLAN

| CONTROL | (L) | ADJUSTMENT RANGE | (A) | SEAL MATERIAL | (N) |
|-----------------------------------------|-----|------------------------------------------------------------------------------|-----|-----------------|-----|
| L Standard Screw Adjustment | | A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting | | N Buna-N | |
| C Tamper Resistant - Factory Set | | B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting | | E EPDM | |
| K Handknob | | C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting | | V Viton | |
| W Hex Wrench Adjustment | | D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting | | | |
| Y Tri-Grip Handknob | | E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting | | | |
| | | W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting | | | |