



This electro-proportional, direct-acting reducer/reliever valve reduces a high primary pressure at the inlet (port 2) to a constant reduced pressure at port 1, with a full flow relief function from port 1 to tank (port 3). The valve is biased to the reducing mode, connecting port 2 to port 1 at a customer specified pressure setting. Increasing the current to the coil will proportionally decrease the reduced pressure at port 1. If pressure at port 1 exceeds the setting induced by the coil, pressure at port 1 is relieved to port 3. This valve is open in the transition from reducing to relieving. It provides good pressure control and dynamic response.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	330 cc/min.
Seal kit - Cartridge	Buna: 990511007
Seal kit - Cartridge	Viton: 990511006

CONFIGURATION OPTIONS

Model Code Example: PRDMXDN

CONTROL	(X)	ADJUSTMENT RANGE	(D)	SEAL MATERIAL	(N)	COIL *
X No Manual Override		D 400 - 200 psi (14 - 28 bar) B 1000 - 400 psi (28 - 70 bar) E 200 - 100 psi (7 - 14 bar) S 100 - 10 psi (0,7 - 7 bar)		N Buna-N V Viton		No coil 212 DIN 43650-Form A, 12 VDC 224 DIN 43650-Form A, 24 VDC 912 Deutsch DT04-2P, 12 VDC 924 Deutsch DT04-2P, 24 VDC

* Additional coil options are available