



This valve is a 4-way, 3-position proportional directional valve. Work ports 2 and 4 are drained to 5 in the center position and port 3 is closed. Pilot pressure at port 1 opposes the spring and creates a variable metering orifice between ports 3 and 4 that is proportional to the pressure at 1. Piloting 6 opens 3 to 2. The force balance of the flow forces, spring and pilot pressure results in a degree of partial self-compensation as the load pressure changes.

Pressure at ports 1 and 6 directly oppose each other.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Pilot Pressure Required for Full Shift at Rated Flow	20 - 23 bar
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	131 cc/min.@70 bar
Pilot Volume Displacement	1,8 cc
Hysteresis	35 %
Seal kit - Cartridge	Buna: 990053007
Seal kit - Cartridge	Viton: 990053006

**CONFIGURATION OPTIONS**

**Model Code Example: FTECXYN**

CONTROL	(X) SPOOL CONFIGURATION	(Y) SEAL MATERIAL	(N) MATERIAL/COATING
<b>X</b> Not Adjustable	<b>Y</b> A and B to T Center <b>W</b> A and B Bleed to T Center	<b>N</b> Buna-N <b>V</b> Viton	Standard Material/Coating /AP Stainless Steel, Passivated