



Closed-center flow divider/combiners are sliding-spool, pressure-compensated devices used to split flow in one direction and combine flow in the opposite direction. These valves may be used to accurately control two or more cylinders or hydraulic motors where bidirectional operation is required.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Divisional Accuracy at Minimum Input Flow	50% ±3.0%
Divisional Accuracy at Max Input Flow	50% ±2.0%
Pressure Drop at Minimum Rated Input Flow	2 bar
Pressure Drop at Maximum Rated Input Flow	24 bar
Seal kit - Cartridge	Buna: 990031007
Seal kit - Cartridge	Polyurethane: 990031002
Seal kit - Cartridge	Viton: 990031006

**CONFIGURATION OPTIONS**

**Model Code Example: FSBAXAN**

CONTROL	(X) FLOW SPLIT	(A) SEAL MATERIAL	(N) MATERIAL/COATING
<b>X</b> Not Adjustable	<b>A</b> 50/50	<b>N</b> Buna-N V Viton	Standard Material/Coating /AP Stainless Steel, Passivated /LH Mild Steel, Zinc-Nickel