



Ventable, pilot-operated, anti shock relief cartridges limit maximum system pressure and also limit the rate of pressure rise. The valve opens and then ramps closed at a constant speed, independent of settings and flows. These 3 port valves include a vent port (port 3) that connects between the main piston and the pilot stage to provide for remote control by other pilot or 2-way valves. The adjust screw determines the maximum (relief) setting and the minimum (threshold) setting.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Factory Pressure Settings Established at	15 L/min.
Maximum Operating Pressure	350 bar
Control Pilot Flow	0,25 - 0,33 L/min.
Pressure Ramp Up Time	300 - 500 ms
Response Time - Typical	2 ms
Adjustment - No. of CW Turns from Min. to Max. setting	4.5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
U.S. Patent #	6,039,070
Seal kit - Cartridge	Buna: 990217007
Seal kit - Cartridge	Polyurethane: 990217002
Seal kit - Cartridge	Viton: 990217006

NOTES Patents are pending for this product.

CONFIGURATION OPTIONS

Model Code Example: RVGTLAN

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
L Standard Screw Adjustment	A 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting	N Buna-N	Standard Material/Coating
C Tamper Resistant - Factory Set	B 500 - 1500 psi (35 - 105 bar), 1000 psi (70 bar) Standard Setting	V Viton	/AP Stainless Steel, Passivated
	C 1000 - 6000 psi (70 - 420 bar), 1000 psi (70 bar) Standard Setting		
	W 1000 - 4500 psi (70 - 315 bar), 1000 psi (70 bar) Standard Setting		